

## Product information

eTEC FibreLite is a 100% fibre-based, premium nano-fluted, corrugated display sheet, with bright white, rigid liners. It's designed as a cost-effective and lightweight, environmentally sustainable sheet for indoor applications.

## Applications

Packaging • Signs and displays • Point of sale • Exhibition panels

## Printing

UV • Latex • Screen printing

## Specification

| PROPERTY   | AVERAGE                |
|--|------------------------|
| Substance (g/m <sup>2</sup> ) ISO536                 | 866                    |
| Calliper (mm) ISO534                                 | 3                      |
| Roughness - printing side (ml/min) ISO/DIS8791-2     | 936                    |
| Roughness - non-printing side (ml/min) ISO/DIS8791-2 | 1535                   |
| Burst ratio (kPA.m <sup>2</sup> /g) ISO2758          | 1,7                    |
| Stiffness MD (mN.m) ISO2493                          | 755                    |
| Stiffness CD (mN.m) ISO2493                          | 586                    |
| Shelf life (unopened)                                | 1 year                 |
| Storage conditions                                   | 8-25°C<br>(35-50% RH)  |
| Application conditions                               | 15-40°C<br>(25-80% RH) |

## Conversion

eTEC FibreLite is suitable for flatbed cutting (oscillate or drag knife), v-groove, CNC, die cutting, guillotining, hand trimming, scoring and folding.

## Stock schedule

| Size            | 3mm |
|-----------------|-----|
| 1220mm x 2440mm | ●   |
| 1524mm x 3050mm | ●   |

## Credentials

